



Modern Wall-hanging Cat Scratcher

Hanging Instructions

Our wall-hanging cat scratcher can be easily installed on most walls. The scratcher comes with four drywall anchors and four screws. Use these anchors when hanging the scratcher on drywall. If mounting directly into wooden wall studs, do not use the wall anchors. Instead, drill a pilot hole and use the screws provided or other appropriate screws.

Hanging Height

There is no specific recommended height for placement of the wall-hanging scratcher. Choose a height and location that is appropriate for your cat. If you have a large cat who likes to stretch, position the scratcher up higher on the wall. For cats who like to scratch lower to the ground, position the scratcher closer to the floor.

Things you'll need:

- Level
- Pencil
- Phillips screwdriver
- 4 wall anchors & screws (included)
- Hanging template (included)

Step 1 Place the enclosed hanging template on the wall where you want to hang the scratcher. Use a level to make sure the arrow is vertical.

Step 2 With a pencil, precisely mark the four points where you will insert the wall anchors.

Step 3 To mount scratcher on drywall, use a Phillips screwdriver to insert the four wall anchors into the points marked on the wall.

Step 4 Remove brackets from scratcher by unscrewing ball knobs. Threaded rods should protrude $\sim\frac{1}{4}$ inch from top and bottom of cardboard pieces. Note: You may need to use a rubber mallet or a hammer covered with a soft cloth to gently tap the end of the threaded rods until $\frac{1}{4}$ inch of rod is protruding from both ends of cardboard. Do not use a metal hammer as this might damage the end of the threaded rod, preventing ball knob from threading properly.

Step 5 Attach both brackets to wall with screws (see diagram).

Step 6 Insert both threaded rods in holes in bottom bracket.

Step 7 Gently press down on cardboard pieces and insert both threaded rods in holes in top bracket. You may need to gently press up on top bracket simultaneously.

Step 8 Screw ball knobs on all four ends of threaded rods and tighten.



Step 1



Step 5



Step 2




Step 6



Step 3



Step 7



Step 4



Step 8

If you have any questions, please contact us at sales@hauspanther.com.

www.hauspanther.com